



# DNH

HEAD OFFICE, NORWAY  
DNH AS

Phone..... + 47 35 98 56 00  
Fax..... + 47 35 98 56 10  
E-mail..... dnh@dnh.no  
Web-Site..... www.dnh.no

ENGLAND  
DNH WW Ltd  
Phone..... + 44 1908 275 000  
Fax..... + 44 1908 275 100  
E-mail..... dnh@dnh.co.uk

GERMANY  
DNH GmbH  
Phone... + 49 040 6569 30-0  
Fax..... + 49 040 6569 30-30  
E-mail..... dnh@dnh.de

USA  
DNH Speakers Inc  
Phone..... + 1 484 494 5790  
Fax..... + 1 484 494 5793  
E-mail..... dnh@dnhspeakers.com

ISO 9001 CERTIFIED

## DSP-15EExmNL(T)

Rear view

Standard Bracket  
Antistatic PA

Optional Bracket  
Stainless steel

All outside nuts and screws in stainless steel

CIRCUIT DIAGRAM


Transformer

Low impedance

Model: MaxPower: DNH 3770 Kragers Norway  
 DSP-15EExmNL(T) 30W  
 DSP-15EExmNL(T) 30W  
 Rated current: 0.26 A IECEx PRE 18.0072X  
 Rated Voltage: 100V Freq: 150-20000Hz  
 P66 & P67 -65C<Ta< 60C  
 Presse 18 ATEX 13498Y Ser.no: Outside enclosure  
 Warning: Do not open while energized CE 0470

Primary nominal tapings		
1 : 2	25,0 W	
2 : 3	15,0 W	
3 : 4	6,5 W	
1 : 3	5,0 W	
2 : 4	2,5 W	
1 : 4	1,5 W	

Standard model delivered with two M20  
Ex approved plastic blinding plugs



Specifications	IIB	IIC
Material / Color	Anti-static PA / Black	
Mounting	Bracket	
Termination	e-chamber, push terminals	
Weight w/transformer	2,8 kg	
IP-rating	66 / 67	
Max. / min. amb. temp	60°C / -50°C	
Rated / max. power	25 W / 30 W	
SPL 1W/1m	109 dB	106 dB
SPL rated power	122 dB	119 dB
Effective freq. range	380 – 7000 Hz	
Dispersion (-6dB) 1kHz / 4kHz	100° / 30° horizontal	
Options	Impedances, labels	

### Installation, Operation and Maintenance Procedures

- Remove lid by four screws, lead cable through the cable gland and connect to terminal with required tapping.
- Check that the gasket is fitted correctly on to the lid. Do not use any lubricants on the gasket.
- Screw lid back into place by four screws with a torque of 1,8 Nm to assure the IP rating.
- To change the position of the loudspeaker, please adjust the standard U- bracket (by loosening / tightening the screws) as required.
- Use only certified/specified cable glands and blanking plugs, reflecting the same IP rating and temperature range as the loudspeaker.
- Standard model delivered with two M20 Ex approved plastic blinding plugs.
- DSP-15 EExmNL(T) can be supplied with three different bracket systems, according to customer requirements.
- For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated.
- Do not open loudspeaker when energized.
- This loudspeaker is supplied with two years warranty against defective workmanship.



DNH reserves the right to alter specifications without notice